

High Efficiency PV Modules / Solar Panels

FEATURES

- Product Warranty: 25 year transferrable power output warranty: 10 years/ 90% 25 year/ 80%
- Cell Type: PolyCrystalline Silicon Photovoltaic
- Panel Construction: High-Efficiency Design Minimizes Weight While Providing a Durable Protective Environment for the Solar Cells
- Weatherproof: Front & Rear Surfaces and Junction Box Completly Sealed From Moisture with Silicone Sealant
- Meets IP65 Requirements: Totally Protected again Dust; Protected against Low-Pressure Jets of Water from all Directions
- Certifications: ISO 9001:2008, IEC 61730

APPLICATIONS

- Secondary Home Power System / Remote Power Electrical Power Back-Up System
- On-Grind Commercial / Industrial Rooftops
- Off-Grid Power System
- Marine & Boating
- Battery Charging
- Pumps / Pool Heating

1 1		0		1 1
╞┻┥┙┩	┙┼─┼		┶┶┷┶┥	
	╺┥┥═┥╴			++
ini				T
┢╼┥╼╼┥		┝┼━┼╴	┝┥──┥┥┥	┽┥
				T
				┶┷
			الالكرك	

ShaanTech *Exercise*

Factory: Shaan Technologies private Limited, Plot No 22, Sector C3, Export Processing Zone Karachi, Pakistan

Phone: +92-21-35080954 Fax: +92-21-35080957 City Sales office : Shaantech Energy Solutions (Pvt) Limited 47/H-1, Block 6, P.E.C.H.S., Karachi. E-mail: info@shaantech.com, Sales-admin@shaantech.net Website: www.shaantech.com

SLR-PNL-300W-301E-P

Peak Output Power (Pmax)	300W	
Power Tolerance Range	0- +5W	
Open Circuit Voltage(Voo	c) 45.2V	
Max.Power Voltage(Vmp)	36.2V	
Short Circuit Current(Isc)	8.71A	
Max.Power current(Imp)	8.30A	
Module Efficiency %	17.04%	
Wind Resistance	3800 Pa	
Max. System voltage	1000V	
Max.Series Fuse Rating	16A	
Weight	23Kg	
Module Application	Class C	
Dimension	1950× 990 × 50mm	

To order ShaanTech Solar products, Please Call our Sales office or contact the Distributor /Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our Nationwide network: www.shaantech.com -2017

Log 090/ R ev 03