

# High Efficiency PV Modules / Solar Panels

PolyCrystalline Solar Panel, 340 Watts

## FEATURES

- ◆ High module efficiency through superior manufacturing technology.
- ◆ No power loss thanks to improved temperature coefficient caused by 5 busbar solar cell.
- ◆ Strictly control the micro-crack of solar cells and the other non visible defect of internal modules.
- ◆ Module can bear snow loads up to 5400Pa and wind loads up to 2400Pa.
- ◆ Manufactured according to and certified international I Quality and Environment Management System.
- ◆ Using advanced low reflection and high light transmission glass and cell sheet surface cutting technology, in the weak light environment can also play a good performance.
- ◆ 10 years product warranty.  
25 years power warranty.

## APPLICATIONS


- ◆ Secondary Home Power System / Remote Power Electrical Power Back-Up System
- ◆ On-Grid Commercial / Industrial Rooftops
- ◆ Off-Grid Power System
- ◆ Marine & Boating
- ◆ Recreational vehicle or Motor Homes / Cabins
- ◆ Battery Charging
- ◆ Pumps / Pool Heating
- ◆ Beacons / Satellite Dishes



## SLR-PNL-340W-101P

Maximum Power at STC(Pmax)	340W
Optimum Operating Voltage (Vmp)	38.53V
Optimum Operating Current (Imp)	8.82A
Open-Circuit Voltage(Voc)	44.98V
Short-Circuit Current (Isc)	9.975A
Solar Cell Efficiency (%)	19.57
Solar Module Efficiency (%)	17.40
Operating Temperature	-40to85°C
Maximum System Voltage	DC1000
Maximum Series Fuse Rating	15A
Power Tolerance	0~+3%

STC:Irradiance 1000W/m<sup>2</sup>, Modules Temperature 25°C, AM=1.5



Factory: Shaan Technologies private Limited,  
Plot No 22, Sector C3, Export Processing Zone  
Karachi, Pakistan

Phone: +92-21-35080954 Fax: +92-21-35080957  
City Sales office : Shaantech Energy Solutions (Pvt) Limited  
47/H-1, Block 6, P.E.C.H.S., Karachi.  
E-mail: info@shaantech.com, Sales-admin@shaantech.net  
Website: www.shaantech.com

To order ShaanTech Solar products, Please Call our Sales office  
or contact the Distributor /Sales Representative in your area.

Visit our website to find your local Distributor or Representative  
from our Nationwide network:


[www.shaantechsolar.com](http://www.shaantechsolar.com)

## Temperature Coefficient and Mechanical Characteristics


## Engineering Drawings

Nominal Operating Cell Temperature (NOCT)	47°C +/- 2°C
Temperature Coefficient of Pmax	-0.47%/°C
Temperature Coefficient of VOC	-0.346%/°C
Temperature Coefficient of ISC	+0.036%/°C

Solar cell	Polycrystalline 156*156mm
No. of cells	72 (6*12) pcs
Dimensions	1956mm*992mm*40mm
Weight	22kg
Front glass	3.2mm tempered glass
Frame	Anodized aluminium alloy
Junction box	IP67 Rated
Connector	MC4 connector
Output cables	PV 4.0mm <sup>2</sup> , 0.9m
1*20'	300pcs
1*40'	/
1*40'HQ	750pcs



## IV-Curves



Factory: Shaan Technologies private Limited,  
Plot No 22, Sector C3, Export Processing Zone  
Karachi, Pakistan

Phone: +92-21-35080954 Fax: +92-21-35080957

City Sales office : Shaantech Energy Solutions (Pvt) Limited

47/H-1, Block 6, P.E.C.H.S., Karachi.

E-mail: info@shaantech.com, Sales-admin@shaantech.net

Website: www.shaantech.com

To order ShaanTech Solar products, Please Call our Sales office  
or contact the Distributor /Sales Representative in your area.

Visit our website to find your local Distributor or Representative  
from our Nationwide network:

[www.shaantechsolar.com](http://www.shaantechsolar.com)